

BULANND

PERSONAL PROTECTION ARMOUR

Article

Brand
Style #

Inherent Flame Resistant Coverall

Bulannd
Bulannd C.55432- 53

Fabric

Volcanide Copolymer 55% + Viscose 43% + AS 2%.

Fiber Type

IFR 1.4 DTEX, Virgin Comfort

Fabric Weight

180 GSM \ 53 OZ

Fabric Standards

NFPA 2112-2023, ISO EN 11612, EN 1149-3, EN 61482-2

Protection

Short Duration Flash Fire.

Arc Rating-ATPV

4.8 cal\cm²

Fabric Standards

NFPA 2112-2023, ISO EN 11612, EN 1149-3, EN 61482-2

Protection

Short Duration Flash Fire.

Arc Rating-ATPV

4.8 cal\cm² EN 61482-2

Fabric Features

Inherent Flame Retardant, Anti Static.
Desert Cool Feature. Cool Breathable.

BULANND

PERSONAL PROTECTION ARMOUR

	Soft Comfort feel ,Highly durable .
Color Fastness	4-5 Excellent
Ecological Standard	OEKO-TEX® standard 100.
Seams Stitch	Double Strong IFR- THREAD
Sizes	XS-4XL
Colors	Orange,Navy Blue, Light Blue, Royal Blue , Grey, Khaki, BEIGE RED , Dyed To Match with MOQ.
Special Features	OIL Water Repellant, BREATHABLE, DUST RESISTANT, QUICK DRY Construction.
Optional Additions	HI Visibility REFLECTIVE Bands. ISO EN 471 1" or 2 " HIRIS TAPE ON SHOULDER , ARMS, LEGS.

FEATURES.:

- 1 2 CHEST POCKETS, with flap & snap closures.
- 2 Two back pockets, RIGHT one with flap .

BULANND

PERSONAL PROTECTION ARMOUR



-
- 3 TOOL POCKET ON RIGHT LEG.
 - 4 ADJUSTABLE CUFFS & ANKLE CONCEALED SNAP BUTTONS.
 - 5 CONCEALED PASS THRU POCKETS ON SIDES.
 - 6 Flexible CONCEALED Elastic Waist.
 - 7 ACTION BACK FOR MECHANICAL STRETCH FLEXIBLE & FREE BODY MOVEMENT.
 - 8 TeleScopic Shoulder for Freedom Movement.
 - 9 CONCEALED STRONG ZIPPER ON FRONT & CONCEALED METAL PARTS.
 - 10 COLLOR LOOP FOR HANGING.
 - 11 HINECK CONCEALED SNAP CLOSURE.
 - 12 PERMA CREASE LINE on Legs.
 - 13 DOUBLE STITCH , BAR TACK REINFORCED ON STRESS POINTS.
 - 14 Front \ Back Embroidery logo .

Garment Designed & Engineered in USA.